

### KPPA-2GHZDP120S-WC

### Configuration

Design Band Type Radiation Pattern Polarization Connector Type Number of Ports Sector Single Directional Vertical/Horizontal N Female

2

### **Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Frequency Range	2,300		2,700	MHz
Input VSWR		1.7:1		
Impedance		50		Ohms
Gain		14.2		dBi
Front to Back Ratio	25			dB
Electrical Downtilt		1.8		Degrees
Cross Polarization Ratio	21			dB
Horizontal (Azimuth) HPBW		120		Degrees
Vertical (Elevation) HPBW		9.8		Degrees
Input Power			50	Watts

**Electrical Specification Notes:** 

Max input power is 50W per port.

### **Mechanical Specifications**

Radome Material Housing Plating/Color

Size Length

Width
Height
Mounting Mast Diameter

Mounting Mast Diameter

Weight

1

Mechanical Specification Notes: Radome material is UV resistant PVC. PVC

Powder Coat

35.6 in [904.24 mm] 8.7 in [220.98 mm] 7 in [177.8 mm]

1.25 to 3.5 in [31.75 to 88.90 mm]


23.4 lbs [10.61 kg]

### **Environmental Specifications**

**Temperature** 

Operating Range -40 to +60 deg C Wind Survivability 100 MPH [160.93 KPH]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 2 GHz 15 dBi Dual Pol H/V 120 Degree Sector Antenna with Radio Case (Cables Included) KPPA-2GHZDP120S-WC





**KPPA-2GHZDP120S-WC** 

Wind Loading

**Plotted and Other Data** 


Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 2 GHz 15 dBi Dual Pol H/V 120 Degree Sector Antenna with Radio Case (Cables Included) KPPA-2GHZDP120S-WC




### **KPPA-2GHZDP120S-WC**

### **Typical Radiation Pattern**



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 2 GHz 15 dBi Dual Pol H/V 120 Degree Sector Antenna with Radio Case (Cables Included) KPPA-2GHZDP120S-WC





### KPPA-2GHZDP120S-WC

### **Appendix**

Electrical Downtilt: Angle in the antenna's elevation pattern in which the maximum gain occurs.

Gain: Antenna's average gain.

Front to Back Ratio @ 180°±30°: Average difference between the antenna's maximum gain and the maximum gain in the antenna's back lobe over ±30° angles.

Cross-polarization Ratio (dB): Typical difference between the co-polarization and cross-polarization gain across the sector's 3 dB Beam Width.

Dedicated to serving the needs of the Wireless Internet Service Provider (WISP) market, KP Performance Antennas offers purpose built products that reliably perform in the field. KP Performance Antennas product line consists of Yagi, Grid, Omni, Dish and other style antennas that operate in the 900 MHz, 2.4 GHz, 3 GHz, and 5 GHz frequencies.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 2 GHz 15 dBi Dual Pol H/V 120 Degree Sector Antenna with Radio Case (Cables Included) KPPA-2GHZDP120S-WC

URL: https://www.kpperformance.com/2-4ghz-120-degree-15-dbi-sector-ubnt-case-p.aspx

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. KP Performance reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. KP Performance does not make any representation or warranty regarding the

suitability of the part described herein for any particular purpose, and KP Performance does not assume liability arising out of the use of any part or document.