

High Gain 700/800 MHz V-POL Omni

- OEM Quality Broadband Performance
 - Rated for 500 Watts Continuous Power
 - -150 dBc PIM Rating
- Stable Electrical performance across entire band
- High quality mechanical package provides IP 66 rating

Available with null-fill and/or beam tilt configurations

Electrical Specifications

Frequency Range	740-870 MHz	
Gain	11.5 dBd	
VSWR (Return Loss)	<1.5:1 (14dB)	
Passive IM 3 rd Order (2x20W)	-150 dBc	
Peak Instantaneous Power (PIP)	25 kW	
Power Input	500 W	
Vertical Beamwidth	5°	
Horizontal Beamwidth	Omni +/-0.5 dB	
Input	7-16 DIN Female	D7
	4.3-10 DIN Female	D4
Beam Tilt	0-10 degree options	

Mechanical Specifications

Configuration	Corporate Fed Dipole Array	
Length	200"	
Radome Diameter	3.0"	
Weight	48 lbs	
Shipping Weight	lbs	
Shipping Dimensions	L	204"
	W	4"
	H	4"
Mounting Area	24 x 3.5 " diam. aluminum	
Suggested Clamps (not included)	PLMTKIT-1	

Environmental Specifications

Operating Temperature	-40° to +140°F (-40°C to 60°C)	
IP Rating	66	
Projected Area	4.25 ft2 (no ice) 5.67 ft2 (with ice)	
Lateral Thrust @ 100mph	170 lbs.	
Wind Gust Rating	150 mph	




ATC-GC7V120-**X-Y-Z**

X = Input Connector [D7 for 7-16 DIN(f); D4 for 4.3-10 DIN(f)]

Y = Beam Tilt [1-10]

Z = Null Fill [NF]

Standard Null Fill Pattern



4° Tilt Pattern

