

High Gain 700/800 MHz V-POL Omni

- OEM Quality Broadband Performance
 - Rated for 500 Watts Continuous Power
 - -150 dBc PIM Rating
- Stable Electrical performance across entire band
- High quality mechanical package provides IP 66 rating
- Available with null-fill and/or beam tilt configurations

Electrical Specifications		
Frequency Range	746-870 MHz	
Gain	8.0 dBd	
VSWR (Return Loss)	<1.5:1 (14dB)	
Passive IM 3 rd Order (2x20W)	-150 dBc	
Peak Instantaneous Power (PIP)	25 kW	
Power Input	500 W	
Vertical Beamwidth	9°	
Horizontal Beamwidth	Omni +/-0.5 dB	
Input	7-16 DIN Female	D7
	4.3-10 DIN Female	D4
Beam Tilt	0-10 degree options	

Mechanical Specifications		
Configuration	Corporate Fed Dipole Array	
Length	115"	
Radome Diameter	3.0"	
Weight	25 lbs	
Shipping Weight	35 lbs	
Shipping Dimensions	L	117"
	W	4"
	H	4"
Mounting Area	12.0 x 3.0" diam. aluminum	
Suggested Clamps (not included)	PLMTKIT-1	

Environmental Specifications	
Operating Temperature	-40° to +140°F (-40°C to 60°C)
IP Rating	66
Projected Area	2.4 ft2 (no ice)
	3.2 ft2 (with ice)
Lateral Thrust @ 100mph	48 lbs.
Wind Gust Rating	150 mph

ATC-GC7V80-X-Y-Z

X = Input Connector [D7 for 7-16 DIN(f); D4 for 4.3-10 DIN(f)]

Y = Beam Tilt [1-10]

Z = Null Fill [NF]



Standard Elevation Pattern

